


AS8 ACTIVE LINE ARRAY PA SYSTEM: TECHNICAL SPECIFICATIONS

Amplifier	
Inputs	2xXLR/TRS Combo's, Stereo 1/8" inputs, dual 1/4" inputs, Bluetooth®
Outputs	XLR balanced line output
Power output	RMS 250W RMS, 1000W peak
Volume	Input Gain control per channel
EQ	Main out 2 band shelving EQ
LEDs	Power/Limiter Indicator
Power Input	100-240V~50/60Hz switchable 250W
Amplifier	Class D amplifier with switching power design
Satellite	Passive full-range speaker
Frequency response	180-20kHz
Max. output SPL	120dB
Impedance	4ohms
Driver	6x2.75" full range line array
Cabinet	ABS plastic
Grill	1.0mm steel
MEAS/G.W.	24.5x14x92.5CM/1PC/6.45KG (SAT) 51x44x48CM/1PC/13.3KG (SUB)
Subwoofer	Active vented subwoofer
Frequency Response	55-200Hz
Max output SPL	116dB (at max. amp output)
Impedance	4 Ohm
Driver	8" subwoofer, 1.5" vc 28Oz
Cabinet	PP plastic
Grill	1.0mm steel
Listings	FCC, CE, & ETL 

Specifications subject to change without any prior written notice.

COMPONENTS & ACCESSORIES

Model # (SKU)	Description
WM219	WM-219 Wireless Microphone System
WM419	WM-419 Wireless Microphone System
VPS564	VPS-80 Microphone
VPS916	VPS-60 Microphone
VPS205	VPS-20 Microphone
PWR571	Pow-R Bar65